



BY:



EcoJet Series

The EcoJet Series provides <u>media free</u> <u>cyclonic filtration</u> that continuously circulates the entire machine tool coolant supply at 20gpm (80lpm) filtering to 5um. This unique and exclusive filtration process keeps the machine tool tank clean and provides clean coolant throughout your machine tool.

No Filters to:

Buy
Store
Dispose Of



Filtration Benefits:

- Improved Chip Management
- Increased Speeds & Feeds
 - Up to 10 Times faster
- Increased Tool Life
 - Up to 15 Times Longer
- Superior Filtration to Increase Coolant Life
- Improved Part Finishes

Available EcoJet Models:

Volume	Pressure	Flow	Filtration	Base Model
8gpm/30lpm	1000psi/70bar	Fixed	10um Bag Cyclonic	EcoJet70
4gpm/15lpm	2000psi/140bar	Fixed	10um Bag Cyclonic	EcoJet140
8gpm/30lpm	300psi/20bar	Fixed	10um Bag	EcoJet20
			Cyclonic	

Dimac

69-71 Williams Rd, Dandenong South VIC 3175, Australia

P: 03 9771 6121 www.dimac.com.au E: Sales@dimac.com.au





Standard Features:

- Unit Volumes: 4-8 gpm (15-30 lpm)
- Unit Pressures: 300-2000 psi (20-140 bar)
- 15gal / 57L Clean Tank
- Electrical Cabinets built to UL/CSA/CE Standards
- 20gpm (80lpm) Continuous Media Free Cyclonic 5um
- One High Pressure Outlet
- Unit Footprint:
 - W-26"x L-26"x H 54" / W 660 x L- 660 x H-1372
- Unit Castor Package
- On Board Grundfos Feeder Pump
- Wiring Harnesses with Machine Side Connectors
- Unit Power to Specification 230v / 460v / 400v

Notes:

Standard filtration is cyclonic and is for use in water soluble coolant only. Be sure to visit us at www.ats-s.com for details on our other filtration options including oil systems.

Ask your ATS Representative about our other product lines –

Work Holding











Air Chucks





6



Toolcha

Rotary Table Units



69-71 Williams Rd, Dandenong South VIC 3175, Australia



P: 03 9771 6121 www.dimac.com.au E: Sales@dimac.com.au