



BY:



EcoClean

The EcoClean provides <u>media free</u> <u>cyclonic filtration</u> that continuously circulates the entire machine tool coolant supply at 20gpm (80lpm) filtering to 5um. This unique and exclusive filtration process keeps the machine tool tank clean and provides clean coolant throughout your machine tool.

Benefits:

- Superior Filtration to increase coolant life
 - 98% Efficiency
- Removes ferrous, non-ferrous and non-metallic particles
- Arrests Bacteria Growth
- Compact Design
- Virtually Maintenance Free
- Improved Pump Life
- Improved Machine Tool Life
- Fast Pay-back
- Environmentally Friendly



No Filters to:

Buy Store Dispose Of

Dimac

69-71 Williams Rd, Dandenong South VIC 3175, Australia

P: 03 9771 6121 www.dimac.com.au E: Sales@dimac.com.au





Standard Features:

- Filtration: 20gpm (80lpm) Continuous Media Free Cyclonic 5um
- Electrical Cabinets built to UL/CSA/CE Standards
- Unit Footprint:
 - W-16"x L-22"x H 54" / W 406 x L- 559 x H-1372
- Unit Castor Package
- On Board Grundfos Feeder Pump
- Wiring Harnesses with Machine Side Connectors
- Unit Power to Spec 120v / 230v / 460v / 400v

Ask your ATS Representative about our other product lines –

Work Holding





















Too

Rotary Table Units



Dimac

69-71 Williams Rd, Dandenong South VIC 3175, Australia

P: 03 9771 6121 www.dimac.com.au E: Sales@dimac.com.au